



## TX-800

Shimano Deore XT 30-speed / Disc

Article	Inch	Frame size	Color
102220011	28"	Gents, 52 cm	slate matt
102220012	28"	Gents, 57 cm	slate matt
102220013	28"	Gents, 62 cm	slate matt

Technical changes and changes in equipment reserved, color deviations possible.

General	<b>Frame</b>	25 CrMo 4, double butted
	<b>Head set</b>	Ritchey Comp Logic V2
	<b>Fork</b>	28" 25CrMo 4
	<b>Shifting System</b>	Shimano Deore XT RD-T8000, 10-speed
	<b>Derailleur</b>	Shimano Deore XT FD-T8000, 3-speed
	<b>Brakes</b>	Shimano Deore XT BR-M8100 (front 180 mm / rear 160 mm)
	<b>Headlight</b>	Busch & Müller Lumotec IQ-XS, 70 LUX
	<b>Rear light</b>	Busch & Müller, Line LED
	<b>Carrier</b>	Tubus Logo Evo / Tubus Tara Lowrider
	<b>Saddle</b>	Selle Royal Scientia
	<b>Seat post</b>	Humpert Ergotec Skalar, patent, aluminum, 27,2 mm, 400 mm, safety level 6
	<b>Pedals</b>	VP-196 aluminum
	<b>Kickstand</b>	Comp Zoom, rear kickstand
	<b>Chainguard</b>	Shimano chainguard
	<b>Mudguard</b>	SKS, plastic
	<b>Other</b>	maximum weight allowed 140 kg
<b>Weight</b>	16,5 kg	
Cockpit	<b>Stem</b>	Humpert Ergotec Piranha 2, 31,8 mm, safety level 6
	<b>Handlebars</b>	Humpert Ergotec Trekking, aluminum, 620 mm, safety level 6
	<b>Grips</b>	Ergon GP3, with clamp and integrated bar ends
	<b>Shift lever</b>	Shimano Deore XT SL-T8000, 3-/10-speed, with gear display
	<b>Brake lever</b>	Shimano Deore XT BL-T8100, 3-finger-lever
Wheels/Tires/Drivetrain	<b>Tires</b>	Schwalbe Marathon Mondial, 47-622, reflex
	<b>Rims</b>	Schürmann YAK19 Disc aluminum, 36 holes
	<b>Spokes</b>	Niro ED 2,34 mm
	<b>Front Hub</b>	Shutter Precision PL-8, hub dynamo, Centerlock, 36 holes
	<b>Rear Hub</b>	Shimano Deore XT FH-M8000, Centerlock, 36 holes
	<b>Sprocket</b>	Shimano Deore XT CS-M771, 10-speed, 11-36 teeth
	<b>Chain</b>	KMC X10
	<b>Inner bearing</b>	Shimano Deore SM-BB52, for Hollowtech II, BSA
	<b>Bottom bracket</b>	Shimano Deore XT FC-T8000, 170 mm, Hollowtech II, 48/36/26 teeth
	<b>Gear ratio (f:r)</b>	48/36/26 teeth : 11-36 teeth