



TX-800

Shimano Deore XT 30-speed / HS33

Article	Inch	Frame size	Color
102220015	28"	Gents, 52 cm	slate matt
102220016	28"	Gents, 57 cm	slate matt
102220017	28"	Gents, 62 cm	slate matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted
	Head set	Ritchey Comp Logic V2
	Fork	28" 25CrMo 4
	Shifting System	Shimano Deore XT RD-T8000, 10-speed
	Derailleur	Shimano Deore XT FD-T8000, 3-speed
	Brakes	Magura HS33, incl. Brakebooster
	Headlight	Busch & Müller Lumotec IQ-XS, 70 LUX
	Rear light	Busch & Müller, Line LED
	Carrier	Tubus Logo Evo / Tubus Tara Lowrider
	Saddle	Selle Royal Scientia
	Seat post	Humpert Ergotec Skalar, patent, aluminum, 27,2 mm, 400 mm, safety level 6
	Pedals	VP-196 aluminum
	Kickstand	0611, rear kickstand
	Chainguard	Shimano chainguard
Mudguard	SKS, plastic	
Other	maximum weight allowed 140 kg	
Weight	16,1 kg	
Cockpit	Stem	Humpert Ergotec Piranha 2, 31,8 mm, safety level 6
	Handlebars	Humpert Ergotec Trekking, aluminum, 620 mm, safety level 6
	Grips	Ergon GP3, with clamp and integrated bar ends
	Shift lever	Shimano Deore XT SL-T8000, 3-/10-speed, with gear display
	Brake lever	Magura HS33
Wheels/Tires/Drivetrain	Tires	Schwalbe Marathon Mondial, 47-622, reflex
	Rims	Schürmann YAK19 aluminum, 36 holes
	Spokes	Niro ED 2,34 mm
	Front Hub	Shutter Precision PV-8, hub dynamo, 36 holes
	Rear Hub	Shimano Deore FH-T610, 36 holes
	Sprocket	Shimano Deore XT CS-M771, 10-speed, 11-36 teeth
	Chain	KMC X10
	Inner bearing	Shimano Deore SM-BB52, for Hollowtech II, BSA
Bottom bracket	Shimano Deore XT FC-T8000, 170 mm, Hollowtech II, 48/36/26 teeth	
Gear ratio (f:r)	48/36/26 teeth : 11-36 teeth	