



T-500

Shimano Deore 30-speed / Disc

| Article | Inch | Frame size | Color |
|-----------|------|---------------|------------|
| 102220131 | 28" | Gents, 52 cm | ebony matt |
| 102220132 | 28" | Gents, 57 cm | ebony matt |
| 102220133 | 28" | Gents, 62 cm | ebony matt |
| 102220134 | 28" | Gents, 67 cm | ebony matt |
| 102220135 | 28" | Ladies, 45 cm | ebony matt |
| 102220136 | 28" | Ladies, 50 cm | ebony matt |
| 102220137 | 28" | Ladies, 55 cm | ebony matt |
| 102220138 | 28" | Ladies, 60 cm | ebony matt |

Technical changes and changes in equipment reserved, color deviations possible.

| General | Component | Specification |
|-------------------------|---|--|
| General | Frame | 25 CrMo 4, double butted |
| | Head set | Ritchey Comp Logic V2 |
| | Fork | 28" aluminum |
| | Shifting System | Shimano Deore RD-T6000, 10-speed |
| | Derailleur | Shimano Deore FD-T6000, 3-speed |
| | Brakes | Shimano Deore BR-M6000 (front 160 mm / rear 160 mm) |
| | Headlight | Busch & Müller Lumotec Eyc, 50 LUX |
| | Rear light | Busch & Müller, Toplight 2C |
| | Carrier | Racktime Light-it |
| | Saddle | Selle Royal Essenza |
| | Seat post | Levelnine, patent, aluminum, 27,2 mm, 300 mm |
| | Pedals | Marwi SP-823 |
| | Kickstand | Comp Zoom, rear kickstand |
| | Chainguard | Shimano chainguard |
| Mudguard | SKS, plastic | |
| Other | maximum weight allowed 140 kg | |
| Weight | 14,1 kg | |
| Cockpit | Stem | Levelnine, aluminum, a-head, 25,4 mm |
| | Handlebars | Levelnine, Trekking, aluminum, 640 mm |
| | Grips | Hermans Grit D33, with clamp |
| | Shift lever | Shimano Deore SL-M6000, 3-/10-speed |
| Brake lever | Shimano Deore BL-M6000 | |
| Wheels/Tires/Drivetrain | Tires | Schwalbe Marathon Supreme, 42-622, reflex |
| | Rims | Schürmann YAK19 Disc aluminum, 36 holes |
| | Spokes | Niro 2,0 mm |
| | Front Hub | Shutter Precision PL-8, hub dynamo, Centerlock, 36 holes |
| | Rear Hub | Shimano Deore FH-M6000, Centerlock, 36 holes |
| | Sprocket | Shimano CS-HG500, 10-speed, 11-32 teeth |
| | Chain | KMC X10 |
| | Inner bearing | Shimano Deore SM-BB52, for Hollowtech II, BSA |
| Bottom bracket | Shimano Deore FC-T6010, 170 mm, Hollowtech II, 48/36/26 teeth | |
| Gear ratio (f:r) | 48/36/26 teeth : 11-32 teeth | |