



## TX-1200

Pinion 18-speed / Disc / Gates

Article	Inch	Frame size	Color
102320001	27.5"	Gents, 52 cm	ebony matt
102320002	27.5"	Gents, 57 cm	ebony matt
102320003	27.5"	Gents, 62 cm	ebony matt

Technical changes and changes in equipment reserved, color deviations possible.

Category	Specification
General	<b>Frame</b> 25 CrMo 4, double butted, Disc, with Pinion-Interface
	<b>Head set</b> Ritchey Comp Logic V2
	<b>Fork</b> 27,5" 25CrMo 4, axle 12 x 100 mm
	<b>Shifting System</b> Pinion P1.18 (max. rider weight 110 kg)
	<b>Derailleur</b> ---
	<b>Brakes</b> Shimano Deore XT BR-M8100 (front 180 mm / rear 180 mm)
	<b>Headlight</b> Busch & Müller Lumotec IQ-X, 100 LUX
	<b>Rear light</b> Busch & Müller, Line LED
	<b>Carrier</b> Tubus Logo Evo / Tubus Tara Lowrider
	<b>Saddle</b> Selle Royal Scientia
	<b>Seat post</b> Humpert Ergotec Skalar, patent, aluminum, 27,2 mm, 400 mm, safety level 6
	<b>Pedals</b> VP-196 Aluminum
	<b>Kickstand</b> Comp Zoom, rear kickstand
	<b>Chainguard</b> Hebie Chainbar für Pinion
	<b>Mudguard</b> SKS, plastic
	<b>Other</b> max load 170 kg
<b>Weight</b> 18.5 kg	
Cockpit	<b>Stem</b> Humpert Ergotec Piranha 2, 31,8 mm, safety level 6
	<b>Handlebars</b> Humpert Ergotec Trekking, Aluminum, 620 mm, safety level 6
	<b>Grips</b> Ergon GP3, with clamp and integrated Barends
	<b>Shift lever</b> Pinion DS2.18, twist shifter
	<b>Brake lever</b> Shimano Deore XT BL-T8100, 3-finger-brake lever
Wheels/Tires/Drivetrain	<b>Tires</b> Schwalbe Marathon Mondial, 50-584, reflex
	<b>Rims</b> Ryde Andra 40 disc aluminum, 32 holes
	<b>Spokes</b> Niro ED 2,34 mm
	<b>Front Hub</b> SON 28, 12 x 100 mm, hub dynamo, Centerlock, 32 holes
	<b>Rear Hub</b> Pinion H3.R X-12, 32 holes
	<b>Sprocket</b> Gates CDX belt pulley, 26 teeth
	<b>Chain</b> Gates CDX-drive belt
	<b>Inner bearing</b> Pinion P1.18
<b>Bottom bracket</b> Pinion Aluminum, 170 mm, with Gates CDX belt pulley 32 teeth	
<b>Gear ratio (f:r)</b> 32 teeth : 26 teeth	