



## TX-800

Shimano Cues 22-speed / Disc

Article	Inch	Frame size	Color
102420011	28"	Gents, 52 cm	slate matt
102420012	28"	Gents, 57 cm	slate matt
102420013	28"	Gents, 62 cm	slate matt

Technical changes and changes in equipment reserved, color deviations possible.

General	<b>Frame</b>	25 CrMo 4, double butted
	<b>Head set</b>	Ritchey Comp Logic V2
	<b>Fork</b>	28" 25CrMo 4, thru-axle 12 x 100 mm
	<b>Shifting System</b>	Shimano Cues RD-U8020, 11-speed
	<b>Derailleur</b>	Shimano Cues FD-U8010, 2-speed
	<b>Brakes</b>	Shimano Deore XT BR-M8100 (front 180 mm / rear 160 mm)
	<b>Headlight</b>	Busch & Müller Lumotec IQ-XS, 70 LUX
	<b>Rear light</b>	Busch & Müller, Line LED
	<b>Carrier</b>	Tubus Logo Evo / Tubus Tara Lowrider
	<b>Saddle</b>	Selle Royal Scientia
	<b>Seat post</b>	Humpert Ergotec Skalar, patent, aluminum, 27.2 mm, 400 mm, safety level 6
	<b>Pedals</b>	VP-196 aluminum
	<b>Kickstand</b>	Comp, rear kickstand
	<b>Chainguard</b>	Shimano chain guard
<b>Mudguard</b>	SKS A56, plastic	
<b>Other</b>	max load 140 kg	
<b>Weight</b>	16.5 kg	
Cockpit	<b>Stem</b>	Humpert Ergotec Piranha 2, 31,8 mm, safety level 6
	<b>Handlebars</b>	Humpert Ergotec Trekking, aluminum, 620 mm, safety level 6
	<b>Grips</b>	Ergon GP3, with clamp and integrated Barends
	<b>Shift lever</b>	Shimano Cues SL-U8000, 2-/11-speed, with display
	<b>Brake lever</b>	Shimano Deore XT BL-T8100, 3-finger brake lever
Wheels/Tires/Drivetrain	<b>Tires</b>	Schwalbe Marathon Mondial, 47-622, reflex
	<b>Rims</b>	Schürmann YAK19 Disc Double Wall Alloy Rim, 36 holes
	<b>Spokes</b>	Niro ED 2,34 mm
	<b>Front Hub</b>	Shutter Precision PL-7, 12 x 100 mm, hub dynamo, Centerlock, 36 holes
	<b>Rear Hub</b>	Shimano XT FH-UR600, Centerlock, 36 holes
	<b>Sprocket</b>	Shimano Cues CS-LG400, 11-speed, 11-45 teeth
	<b>Chain</b>	Shimano CN-LG500
	<b>Inner bearing</b>	Shimano BB-MT501B, for Hollowtech II, BSA
<b>Bottom bracket</b>	Shimano Cues FC-U8000-2, 170 mm, Hollowtech II, 46/32 teeth	
<b>Gear ratio (f:r)</b>	46/32 teeth : 11-45 teeth	