



T-100 Sport

Shimano Cues 18-speed / Disc

Article	Inch	Frame size	Color
102420251	28"	Gents, 52 cm	ebony matt
102420252	28"	Gents, 57 cm	ebony matt
102420253	28"	Gents, 62 cm	ebony matt
102420255	28"	Ladies, 45 cm	ebony matt
102420256	28"	Ladies, 50 cm	ebony matt
102420257	28"	Ladies, 55 cm	ebony matt

Technical changes and changes in equipment reserved, color deviations possible.

General	
Frame	25 CroMo 4
Head set	Ritchey Comp Logic V2
Fork	28" aluminum
Shifting System	Shimano Cues RD-U3020, 9-speed
Derailleur	Shimano Cues FD-U4010, 2-speed
Brakes	Shimano BR-MT200 (front 160 mm / rear 160 mm)
Headlight	Busch & Müller Lumotec Dopp N plus, 35 LUX
Rear light	Busch & Müller, Toplight 2C
Carrier	vsf fahrradmanufaktur Basic Tour 2.0, strutless, with spring flap, compatible with Racktime Snap-It 2.0 System
Saddle	Selle Royal Rio
Seat post	Humpert Ergotec Atar, patent, aluminum, 27.2 mm, 300 mm
Pedals	Marwi SP-811
Kickstand	Zoom, rear kickstand
Chainguard	Shimano chain guard
Mudguard	SKS A42, plastic
Other	max load 140 kg
Weight	15.4 kg
Cockpit	
Stem	Levelnine, aluminum, a-head, 31,8 mm
Handlebars	Levelnine, Trekking, aluminum, 640 mm
Grips	Herrmans Grit DD33, with clamp
Shift lever	Shimano Cues SL-U4000, 2-/9-speed, with display
Brake lever	Shimano Altus BL-MT200, 3-finger brake lever
Wheels/Tires/Drivetrain	
Tires	Schwalbe Marathon Citizen, 37-622, reflex
Rims	Schürmann YAK19 Disc Double Wall Alloy Rim, 36 holes
Spokes	Niro 2,0 mm
Front Hub	Shimano DH-3D37, hub dynamo, Centerlock, 36 holes
Rear Hub	Shimano FH-QC300-HM, Centerlock, 36 holes
Sprocket	Shimano Cues CS-LG300, 9-speed, 11-36 teeth
Chain	Shimano CN-LG500
Inner bearing	Shimano BB-MT501B, for Hollowtech II, BSA
Bottom bracket	Shimano Cues FC-U4010-2, 170 mm, Hollowtech II, 46/30 teeth
Gear ratio (f:r)	46/30 teeth : 11-36 teeth