



GX-500

SRAM Apex XPLR 12-speed / Disc

| Article | Inch | Frame size | Color |
|-----------|------|--------------|-----------------------|
| 102420548 | 28" | Gents, 48 cm | dry terracotta glossy |
| 102420551 | 28" | Gents, 51 cm | dry terracotta glossy |
| 102420554 | 28" | Gents, 54 cm | dry terracotta glossy |
| 102420557 | 28" | Gents, 57 cm | dry terracotta glossy |
| 102420560 | 28" | Gents, 60 cm | dry terracotta glossy |

Technical changes and changes in equipment reserved, color deviations possible.

| | | |
|-------------------------|---|---|
| General | Frame | 25 CrMo 4, double butted |
| | Head set | Acros AZX-228, 1 1/8"-1,5", External Cup |
| | Fork | vsf fm Gravel 28" aluminum, 12 x 100 mm, Flatmount, tapered |
| | Shifting System | SRAM Apex XPLR , 12-speed |
| | Derailleur | --- |
| | Brakes | SRAM Apex (front 160 mm / rear 160 mm), Flatmount |
| | Headlight | --- |
| | Rear light | --- |
| | Carrier | --- |
| | Saddle | Selle Italia Model Y |
| | Seat post | Ritchey WCS Carbon Link Flexilogic, 27,2 mm, 350 mm |
| | Pedals | --- |
| | Kickstand | --- |
| | Chainguard | --- |
| Mudguard | --- | |
| Other | max load 120 kg, vsf fahrradmanufaktur Enamel-Mug | |
| Weight | 11,5 kg | |
| Cockpit | Stem | Levelnine, aluminum, 6°, (90 / 90 / 90 / 110 / 110 mm) |
| | Handlebars | Levelnine Gravel, aluminum, Flare 12°, (440 / 440 / 440 / 460 / 480 mm) |
| | Grips | Fizik Vento Solocush Tacky handlebar tape, 2,7 mm thick, black |
| | Shift lever | SRAM Apex, 12-speed |
| | Brake lever | SRAM Apex, 12-speed |
| Wheels/Tires/Drivetrain | Tires | Schwalbe G-One R, 45-622 |
| | Rims | Ryde DP19, Disc, 32 holes |
| | Spokes | Niro 2,0 mm black |
| | Front Hub | KT, 12 x 100 mm, Centerlock, 32 holes |
| | Rear Hub | KT, 12 x 142 mm , Centerlock, 32 holes |
| | Sprocket | SRAM XPLR PG-1231, 12-speed, 11-44 teeth |
| | Chain | SRAM Apex, 12-speed |
| | Inner bearing | SRAM DUB, BSA |
| | Bottom bracket | SRAM Apex, 40 teeth, 170 mm |
| Gear ratio (f:r) | 40 teeth : 11-44 teeth | |